

# STONEWARE ROBE LIMESTONE



Concrete Pavers • Stone Pavers • Tiles • Garden Walls & Edging  
Retaining Walls • Concrete Sleepers • Concrete Blocks • Wall Cladding



# STONEWARE ROBE LIMESTONE



## FEATURES

- Strong and durable
- Salt, slip, scratch resistant
- Mild acid resistant
- Free samples available

## SUITABLE FOR

- Indoor and outdoor applications
- Pool areas
- Patios and alfresco
- Garden paths and walkways

| Specifications       | Size (h x w x d) | No. per m <sup>2</sup> | Slip Rating | Weight per m <sup>2</sup> | m <sup>2</sup> per pallet/unit |
|----------------------|------------------|------------------------|-------------|---------------------------|--------------------------------|
| Paver                | 600 x 300 x 20mm | 5.55                   | R11         | 46kg                      | 28.8                           |
| Paver                | 600 x 600 x 20mm | 2.78                   | R11         | 46kg                      | 28.8                           |
| Tile                 | 600 x 600 x 10mm | 2.78                   | R10         | 23kg                      | 57.6                           |
| Tile                 | 600 x 300 x 8mm  | 5.55                   | P4          | 18.4kg                    | 51.84                          |
| Tile                 | 600 x 600 x 8mm  | 2.78                   | P4          | 18.4kg                    | 51.84                          |
| Bullnose & Aris Edge | 600 x 600 x 20mm | N/A                    | R11         | 16.5kg each               | 80 units                       |
| 70mm Drop Face       | 600 x 300 x 20mm | N/A                    | R11         | 10.18kg each              | 48 units                       |
| 70mm Drop Face       | 600 x 600 x 20mm | N/A                    | R11         | 18.83kg each              | 24 units                       |

## COLOUR RANGE\*

Robe Limestone



Due to natural resources used in production there are slight colour variations between batches. Pool copings can differ in appearance to the body tile and mixing 2 different sizes can end up with slight variations. Colour swatches are a guide only. Samples you receive may also be slightly different to what is received. Stoneware pavers should be laid with approximately 2-3mm gap to avoid chipping. This product has a V2 Variance rating. Please refer to the charts below.



[www.australianpaving.com.au](http://www.australianpaving.com.au)

  [australianpavingcentre](https://www.australianpavingcentre.com.au)

